

AXS-200

part of the SharpTESTER Access Line

NETWORK TESTING – ACCESS



**The new authority in access network testing:
designed for multilayer testing on both
copper and optical fiber**

Efficiency and Simplicity

- One-touch test start/stop
- A single user interface for all SharpTESTER module series
- Flexible architecture adapting to evolving customer requirements
- Rugged, weather-proof design
- Easy to use, even for technicians who are inexperienced or unfamiliar with specific applications
- Fast and clear pass/fail results on a transfective graphical color display

A Multilayer, Multimedium Test Solution— Three Module Series

Copper/DSL/Triple-Play

- Complete local loop testing
- xDSL QoS assessment of triple-play services
- Ethernet testing for triple-play services

Optics

- Physical-layer testing within fiber access links

Ethernet

- Installation and maintenance testing for Ethernet circuits

Flexible Connectivity

- Easy file transfer and software upgrade through USB connection
- USB A/B and RJ-45
- Fiber inspection probe port

SPECIFICATIONS

Display	89 mm (3.5 in) LCD, 320 x 240, QVGA, advanced TFT	
Interfaces	USB host/client, RJ-45 Ethernet 10/100, video fiber inspection probe port	
Storage	Internal: 512 MB; USB: 1 Gbit, 2 Gbit and more	
Battery	Smart rechargeable Li-Ion	
Power supply	15-24 VDC, 40 W minimum	

GENERAL SPECIFICATIONS

Temperature	operating	-10 °C to 50 °C	(14 °F to 122 °F)
	storage ^a	-40 °C to 70 °C	(-40 °F to 158 °F)
Size (H x W x D)	241.3 mm x 109.2 mm x 38.1 mm		(9 1/2 in x 4 5/16 in x 1 1/2 in)
Weight	0.468 kg		(1.02 lb)
Relative humidity	0 % to 93 %, non-condensing		
Warranty	1 year		

Note

a. Maximum of 60 °C (140 °F) for the internal battery.

ACCESSORIES

GP-10-061	Soft case
GP-10-072	Semi-rigid carrying case
GP-10-074	Rigid carrying case AXS-200
GP-2016	RJ-45 LAN cable (10 feet)
GP-2019	USB microdrive (1 Gbit)

ORDERING INFORMATION

AXS-200-XX-XX

Model ■

AXS-200 = SharpTester

Probe ■

FP = Probe option

FP5 = Probe connector cable and 200x/400x probe

■ **PSWO**

00 = Without software option

FPS^a = Fiber Inspection probe software

Note

a. Mandatory with FPS.

Example: AXS-200-FP5-FPS

EXFO Corporate Headquarters > 400 Godin Avenue, Quebec City (Quebec) G1M 2K2 CANADA | Tel.: 1 418 683-0211 | Fax: 1 418 683-2170 | info@EXFO.com

Toll-free: 1 800 663-3936 (USA and Canada) | www.EXFO.com

EXFO America	3701 Plano Parkway, Suite 160 Plano, TX 75075 USA	Tel: 1 800 663-3936	Fax: 1 972 836-0164
EXFO Europe	Omega Enterprise Park, Electron Way Chandlers Ford, Hampshire S053 4SE ENGLAND	Tel: +44 2380 246810	Fax: +44 2380 246801
EXFO Asia	151 Chin Swee Road, #03-29 Manhattan House SINGAPORE 169876	Tel: +65 6333 8241	Fax: +65 6333 8242
EXFO China	No.88 Fuhua, First Road Central Tower, Room 801, Futian District Beijing New Century Hotel Office Tower, Room 1754-1755 No. 6 Southern Capital Gym Road	Shenzhen 518048, CHINA Beijing 100044 P.R. CHINA	Tel: +86 (755) 8203 2300 Tel: +86 (10) 6849 2738 Fax: +86 (755) 8203 2306 Fax: +86 (10) 6849 2662

EXFO is certified ISO 9001 and attests to the quality of these products. This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. EXFO has made every effort to ensure that the information contained in this specification sheet is accurate. All of EXFO's manufactured products are compliant with the European Union's WEEE directive. For more information, please visit www.EXFO.com/recycle. However, we accept no responsibility for any errors or omissions, and we reserve the right to modify design, characteristics and products at any time without obligation. Units of measurement in this document conform to SI standards and practices. Contact EXFO for prices and availability or to obtain the phone number of your local EXFO distributor.

For the most recent version of this spec sheet, please go to the EXFO website at <http://www.EXFO.com/specs>

In case of discrepancy, the Web version takes precedence over any printed literature.