

TBS190BDV SDI, DV & Composite synchronizer

Broadcast quality synchronizer and time base stabilizer with AES and embedded audio

The **TBS190BDV** is a multi-standard broadcast quality synchronizer, noise reducer and time base stabilizer with SDI, DV, composite and YC interfaces. Embedded audio is processed as well as providing balanced AES audio interfaces. Featuring 12-bit sampling, 10-bit processing and rugged inputs, the TBS190BDV is equally suited to digitizing broadcast grade sources as with unstable, noisy sources.

Full Product List

Base Model

Kudos Plus TBS190BDV
(3548606)

The TBS190BDV is a multi-standard broadcast quality synchronizer, noise reducer and time base stabilizer with SDI, DV, composite and YC interfaces, 12 bit sampling and 10 bit processing featuring embedded and balanced AES audio

Base Model

Kudos Plus TBS190BDV
(3548606-RM)

As above, with rack mount kit

Option

Rack mount kit
(INSY-MNT-KIT)

Rack mount kit to mount one or two units in a 19" rack




Features

- SDI, DV, Composite & YC Synchronization
- Time base stabilization
- Adaptive recursive Noise Reduction with automatic noise level detection
- 12-bit decoding with 5-line comb filter
- 12-bit encoding
- Inputs PAL, NTSC, NTSC-J, NTSC4.4, PAL-N, PAL-M, SECAM with automatic input detection
- Outputs PAL, NTSC, NTSC-J, PAL-N, PAL-M
- 4 channel (2 pair) embedded audio processing
- Seamless PCM audio tracking delay with manual offset – up to 2.5s
- Pass through for all HANC/VANC data
- Composite inputs tolerant to noise & errors

- Unique genlock 'Floating mode**'
- RollCall compatible via USB link

Applications

- Universal Analog / Digital interface
- Audio embedding & extraction
- Satellite down-link & radio links
- Ingest / PC capture pre-processing
- Duplication
- VHS dubbing
- Format conversion



Inputs and Outputs

Video Input

2 x SDI	525/625 line with automatic detection(BNC)
2 x Composite	27MHz, 12-bit sampling PAL, NTSC, NTSC-J, NTSC4.4, PAL-N, PAL-M, SECAM with automatic detection(BNC)
1 x YC	27MHz, 12-bit sampling PAL, NTSC, NTSC-J, NTSC4.4, PAL-N, PAL-M with automatic detection (Mini DIN4)
Reference	Composite or Y (BNC loop-through)

Video Output

2 x SDI	525/625 line(BNC)
2 x Composite	27MHz, 12-bit D to A. Output Formats PAL, NTSC, NTSC-J, PAL-N, PAL-M(BNC)
1 x YC	27MHz, 12-bit D to A. Output Formats PAL, NTSC, NTSC-J, PAL-N, PAL-M (Mini DIN4)

Video Input/Output

1 x DV	4 pin DV connector. (will not simultaneously decode and encode) with 32, 44.1 or 48kHz audio – one pair
--------	---

Audio Inputs & Outputs

2 x AES input	Balanced (2-part screw terminal) 32-96kHz PCM audio
2 x AES output	Balanced (2 part screw terminal) 48kHz PCM audio

Remote control

RollCall via USB link to a PC

Control Features

Input Select	SDI A,B; DV; Composite A, B; YC
Audio Source (1)	SDI pair 1-8; DV; External 1-2
Audio Source (2)	SDI pair 1-8; DV; External 1-2
Audio Destination	SDI group 1-4
DV Audio Encode	From processed pair 1-2
Add Audio Delay	0ms to +2.5s
Noise Reduction	Y;C (Off; 1; 2; 3; Max)
Split Screen	Off/On (view noise reduction)
Vertical Enhance	Off; 1; 2; 3 (max)
Horizontal Enhance	-2; -1; 0; 1; 2; 3 (max)
Input Standard NTSC	NTSC, NTSC-J
Composite Output	PAL, NTSC, NTSC-J, PAL-N, PALM
Freeze	Freezes next frame (sync mode)
Field Freeze	Freezes next field
Luminance Gain	Preset; ± 6dB
Chrominance Gain	Preset; ± 6dB
Black Level	Preset; ± 100mV
NTSC Hue	Preset; ± 30 degrees
Genlock Phase	Preset; approx. ±1 line

Genlock Mode	Lock to reference; Lock to input; Float (stabilized) - if same line standard; Free-run
Output Pattern	Black; Color Bars
Default Output	When input is lost; go to black; go to color bars
Decoder / Encoder	AGC, ACC, comb, DNR, CTI
DV features	Audio sample rate; AVC (play/record/stop/forward/rewind)

Indication / Monitoring (also Logging / RollTrack)

Input Standard	Present; Standard
Reference	Present; Error (Error indicated if the reference is not the same line standard as the input)
Power	Standby

Rollcall

All Control features available from rollcall via PC USBshare application. Indication/monitoring parameters are available for Logging and Rolltrack

System Parameters

Processing	≥10 bit
SDI Input Switch	Tolerant to SMPTE RP168 vertical interval switch.
SDI Data	All HANC & VANC data passed
Vertical Interval	All luminance data passed when input & output are the same standard
Reference Lock Range	Greater than ±80ppm

Mechanical

Dimensions	½ 1RU rack (44x220x250mm)
Temperature	0°C to 35 °C operating -20 °C to +70 °C storage

Floating Mode - Without a reference the output will either free-run or lock to a stabilized input sync if operating in synchronize mode. In this stabilized or 'floating mode' the output will always follow shortly after the input, so preventing lip-sync errors and frame drop / repeat. The inputs are highly tolerant to unstable and noisy sources, while the synchronizer always creates correctly aligned images, even during sync disturbances and asynchronous input switches

Snell & Wilcox Inc.
3519 Pacific Ave.
Burbank, CA 91505
Tel: +1 818 556 2616
Fax: +1 818 556 2626
info@snellamerica.com


Snell & Wilcox Ltd.
Southleigh Park House,
Eastleigh Road, Havant,
Hampshire PO9 2PE, UK
Tel: +44 (0) 23 9248 9000
Fax: +44 (0) 23 9245 1411
info@snellwilcox.com

Snell & Wilcox (Hong Kong) Ltd.
Room 603, Tai Tung Building,
No.8 Fleming Road,
Wanchai, Hong Kong
Tel: +852 2356 1660
swhk@snellwilcox.com.hk

Company policy is one of continuous product improvement. Specifications are therefore subject to change without notice.

Snell & Wilcox and Putting Pictures to Work are trademarks of the Snell & Wilcox Group. All other trademarks mentioned herein are duly acknowledged.

© 2006 Snell & Wilcox Limited
All Rights Reserved



KP05 02/06 V1