

TopCon Quadro Power Supply

Programmable High-Power DC Supply



TopCon Quadro Power Supply unit with optional front panel control unit HMI

- Constant voltage (0 – 100 %), constant current (0 – 100 %) and constant power operation (5 – 100%) with automatic and fast crossover and mode indication. Internal resistance simulation.
- Finely graduated product line: 52, 65, 100, 130, 200, 400, 500, 600, 800, 1000 VDC. Power categories of 10, 16, 20 and 32 kW are available for each nominal output voltage.
- Optional extras and accessories complete the product line of power supply units.
- Modular concept for easy power increase: Parallel, series or multiloading master-slave-operation for up to eight power supply units.
- High efficiency at a low cost, resulting from the application of innovative IGBT and transformer technology. Primary switched. Galvanic isolated. Full digital control and regulation.
- A user-friendly PC program, the operating and service software TopControl, enables the user to communicate with the power supply.
- TopControl installation file, LabVIEW[®] and C/C++ API (DLL file) are included in the scope of delivery.
- CE conformity
- Swiss made: Further developed, manufactured and tested in Switzerland by Regatron AG.

Regatron AG

Kirchstrasse 11
CH-9400 Rorschach
Switzerland
Tel +41 71 846 67 67
Fax +41 71 846 67 77
www.regatron.com
topcon@regatron.ch

10 kW / 200 VDC / 63 A

TC.P.10.200.400.S

Mains requirements and output specifications

AC line input

Line voltage.....3 x 360 – 440 VAC
Line frequency 48 – 62 Hz
Mains connection type3L+PE (no neutral)
Input current..... 3 x 20 Arms¹⁾
Leakage current L to PE < 10 mA

Output ratings

Output power range0 – 10 kW
Output voltage range0 – 200 VDC
Output current range0 – 63 A²⁾
Internal resistance range 0 – 1000 mΩ³⁾

Operating modes

Voltage regulation (CV).....0 – 100 % U_{max}
Current regulation (CC)..... 0 – 100 % I_{max}
Power regulation (CP).....5 – 100 % P_{max}

Static accuracy

Load regulation CV, CC< ± 0.1 % FS⁴⁾
Line regulation CV, CC< ± 0.1 % FS⁵⁾

Transient response time

Load regulation CV, CC< 2 ms⁶⁾
Set value tracking CV, CC< 2 ms⁷⁾

Stability

CV, CC.....< ± 0.05 % FS⁸⁾

Temperature coefficient

CV.....< 0.02 % FS / °C⁹⁾
CC.....< 0.03 % FS / °C⁹⁾

Output ripple

300 Hz V_{pp}< 1.1 % FS¹⁰⁾
300 Hz V_{rms}< 0.4 % FS¹⁰⁾

Output noise

40 kHz – 1 MHz V_{pp}< 1.5 V¹⁰⁾
40 kHz – 1 MHz V_{rms}< 0.1 V¹⁰⁾

Remote sensing

Terminals on rear side Line voltage drop compensation

General specifications

Efficiency at nominal power 92 %
Weight.....44 kg
Width front panel.....483 mm
Width housing (19") 444 mm
Height front panel.....265 mm
Height housing (6 U) 262 mm
Depth with output terminals.....495 mm
Depth housing.....450 mm
Line input connections:terminal block 4 x 10 mm²
Output terminals: nickel-plated copper bars, length: 40 mm, 1 hole 9 mm Ø in each bar

- 1) At nominal output power and line input voltage 3 x 390 VAC / 50 Hz. Soft-start to limit turn-on surge currents.
- 2) Current according to the given power limit of the corresponding units. ($P = U_{out} \cdot I_{out} \leq 10 \text{ kW}$; for $I_{out} > 50 \text{ A} \rightarrow U_{out} < 200 \text{ V}$).
- 3) Optionally extendable to a maximum of 12000 mΩ
- 4) Typical value for 0 – 100 % load variation, at constant line input and temperature conditions.
- 5) Typical value for input voltage variation within 360 – 440 VAC, at constant load and temperature conditions.
- 6) Typical recovery time to within < ± 5 % band of set value for a load step 10 – 90 %, ohmic load, at constant line input and temperature conditions. Transient response time can be slightly affected by multi-unit operation.
- 7) Typical recovery time to within < ± 5 % band of set value for a set value step 10 – 90 %, ohmic load, at constant line input and temperature conditions. Transient response time can be slightly affected by multi-unit operation.
- 8) Maximum drift over 8 hours after 30 minute warm-up time, at constant line input, load and temperature conditions.
- 9) Typical change of output values versus ambient temperature, at constant line input and load conditions.
- 10) Typical value at nominal ohmic load, line asymmetry < 1 V_{rms}.

Non-ohmic loads can lead to deviations in the technical data. All product specifications are subject to change without notification.

Ambient conditions

Operating temperature 5 – 40°C
 Storage temperature -25 – 70°C
 Relative air humidity (non-condensing) 0 – 95 %

Cooling

Standard: internal temperature-controlled fans
 Optional: integrated liquid cooling of the power stage,
 heat exchanger material: AC100 (Al-Ti-alloy),
 inlet / outlet on rear side, size: G 1/2"

Protection**Built-in protection**

Overvoltage protection
 (programmable) 0 – 110 % U_{max}
 Overcurrent protection
 (programmable) 0 – 110 % I_{max}
 Max. reactive load voltage ≤ 110 % U_{max}
 Short circuit protection Cont. short circuit allowed
 Internal diagnostics: line input conditions, transform-
 er primary current, temperature conditions, processor
 idle time, system configuration, system communica-
 tion, sensor signals, power semiconductors

Type of protection (IEC 60529)

Basic construction IP 20 (current bars on
 rear side excluded)
 Mounted in cabinet Up to IP 53

Conformity CE-Marking**EMC Directive**

EMC emission EN 61000-6-4
 EMC immunity EN 61000-6-2

Low Voltage Directive

Electronic equipment
 for use in power installations EN 50178

Isolation

Line to output 4000 Vrms
 Line to case 2500 Vrms
 Output to case > 10 MΩ / 2 x 6.8 nF
 - bar ¹⁶⁾ + 1000 VDC / - 1000 VDC
 + bar ¹⁶⁾ + 1000 VDC / - 1000 VDC

Standard programming interfaces**Control port**

Isolation to electronics and earth: 125 Vrms
 25 pin D-sub connector, female, on rear panel

Control port input functions

Output voltage on / off 0 / 24 VAC / DC
 2 digital application inputs 0 / 24 VAC / DC ¹²⁾
 Interlock circuit 0 / 24 VDC
 Voltage setting 0 – 100 % 0 – 10 V
 Current setting 0 – 100 % 0 – 0 V
 Power setting 0 – 100 % 10 – 0 V
 Int. resistance setting 0 – 1000 mΩ ³⁾ 0 – 10 V

Control port output functions

Unit ready / error Relay contact
 Output voltage on Relay contact
 Temperature warning Relay contact
 Actual voltage readback 0 – 100 % 0 – 10 V
 Actual current readback 0 – 100 % 0 – 10 V
 Resolution (programming
 and readback): U, I, P, Ri 0.2 % FS

Standard programming interfaces (continued)**RS232**

9 pin D-sub connector, female, on front panel
 Isolation to electronics and earth 125 Vrms
 Baud rate 38400 baud
 Resolution (programming and readback):
 U, I 0.025 % FS
 P, Ri 0.1 % FS

Ordering Information**Ordering code**

TC.P.10.200.400.S(.Option)

Standard Scope of delivery

TopCon power supply unit ready to install, including:
 Operating manual (English or German)
 RS232 cable 1.8 m
 Installation disc TopControl,
 LabVIEW[®] and C/C++ API (DLL file)

Options**Front panel control unit HMI**

Integrated control, programming and display unit with
 graphic LC-Display, select wheel, push buttons and
 interactive text menus
 Languages (switchable) English, German
 Display resolution:
 U 4 digits
 I 3 digits
 P Kilowatt + 1 decimal digit
 Ri 1 mΩ

Remote control unit RCU

Specifications same as HMI, available in 2 versions:
 desk top and 19" rackmount
 max. cable length 40 m
 Desk top W x H x D 355 x 100 x 290 mm
 19" rackmount W x H x D .. 483 x 133 (3 U) x 290 mm

Further options

TFEAAPControl Function Generating Engine
 Time-based and Parametric Pr.
 SASControl SAS Application Program
 including TFEAAP
 AccuControl Battery Application Program
 RS232REAR¹³⁾ RS232 On Front and Rear Panel
 USB¹⁴⁾ Interface USB on Rear Panel
 RS422¹³⁾ RS422 on Rear Panel
 ETHERNET¹⁵⁾ Ethernet to RS232 Converter
 External converter unit,
 IEEE¹⁴⁾ GPIB/ IEEE488.2/ SCPI on Rear Panel
 cannot be combined
 with CANOPEN nor with USB
 CANOPEN¹⁴⁾ CAN/ CANOPEN on Rear Panel
 PROFIBUS¹⁵⁾ ... Profibus DP 485 to RS232 Converter
 external unit
 CANCEABLE Connecting Cable
 for Multi-Unit Operation or RCU: 2, 5, 10 m
 PACOB Protection against Accidental contact
 IRXTS³⁾ Internal resistance range extension
 LCAL Integrated liquid cooling of the power
 stage, inlet / outlet on rear side, size G 1/2"
 AIRFILTER Front Panel Airfilter 6 U / 9 U
 ISR Integrated Safety Relay
 NSOV Non-Standard Output Voltage (if possible)

- 11) Ambient temperature or CDF restrictions: refer to output ratings.
- 12) Customer-specifically programmable.
- 13) This option and RS232: time-shared mode required, if used together.
- 14) RS232 only on Rear Panel.
- 15) Please order option RS232REAR separately.
- 16) Peak Voltage including DC-Output Voltage.