

Automatic Adaptive Core Fusion Splicer

T-55



Fast, Capable, Practical

Fast Splicing 7sec / Heating 20sec



Detachable Case
for Working Tray



Touch Screen
Control Panel



Durable & Rugged

Specifications

Items		T-55
Optical fiber requirements	Material	Silica glass
	Fiber count / Profile types	Single / SMF (G.652), MMF (G.651), DSF (G.653), NZDSF (G.655), BIF (G.657)
	Fiber diameter	Cladding diameter : 80-150μm, Coating diameter: 100 - 1,000μm
	Cleave length	5 - 16mm with coating clamp
Standard performance	Splice loss (typical) *1	SMF : 0.02dB, MMF : 0.01dB, DSF : 0.04dB, NZDSF : 0.04dB
	Return loss (typical)	60dB or greater
	Splice time (typical)	7sec (SM G652 Quick Mode), 9sec (Auto Mode)
	Heating time (typical)	20sec (FPS-61-2.6 sleeve, Slim 60mm Quick Mode)
	Splice & Heat cycles per battery full charge *2	Approx. 230 (BU-11)
	Fiber view & magnification	2 CMOS cameras observation, 200X (zoom: 525X) for X or Y single axis view, 88X for both X & Y dual axis view
	Proof test	1.96 - 2.09N
	Applicable sleeve length	Up to 60mm sleeves
Programs	Splice programs	Max. 300 (300, 23 are pre-optimised, 277 editable by user)
	Heating programs	Max. 100 (100, 19 are pre-optimised, 81 editable by user)
Functions	Splice image capture / Splice data storage	200 images / 10,000 splice data in splicer it self (without SD card)
	Attenuation splicing	0.1dB to 15dB in 0.1dB increments
	Universal clamps	Provided, 250μm, 900μm tight & loose buffer fiber
	Reversible coating clamps	Provided
	Onboard user training video	Provided
	Automatic fiber identification	SMF / MMF / Other
Size / Weight	Automatic arc calibration	Automatically compensates for environmental condition changes
	Size	120(W) x 154(D) x 130(H) mm (without anti-shock rubber)
	Weight	1.7kg (without Battery), 1.9kg (with Battery BU-11S) / 2.0kg (with Battery BU-11)
	Monitor	4.1" touch screen color LCD display
Terminals	DC output	DC 12V (for JR-6)
	USB port	USB 2.0 (mini-B type)
Power supply	Storage media	SD / SDHC memory card MAX32GB
	AC input	AC 100 - 240V, 50/60Hz (ADC-1430S)
	DC input	DC 10 - 15V
	Battery pack	Li-ion 11.1V, 2,300mAh (BU-11S) / Li-ion 11.1V, 4,600mAh (BU-11)
Operating condition		Altitude : 0 - 6,000m, Temperature : -10 ~ +50°C, Humidity : 0 - 95% (non-condensing), Wind velocity : up to 15m/sec
Storage condition		Temperature : -40 ~ +80°C, Humidity : 0 - 95% (non-condensing), Battery : -20 ~ +30°C (long term)
Electrode life *3		3,000 arc discharges
Software updates		Internet
Data management		Can be stored, edited and analyzed by dedicated PC software

*1 : Average value of the final inspection in room temperature with Sumitomo identical fiber.

Measured by cut-back method relevant to ITU-T and IEC standards.

*2 : Splice & Heat cycles may vary depending on the battery status and the operating environment.

*3 : Electrode life may vary depending on the operating environment.

Environmental Durability*

Test details	
Shock resistance	Drop from 76cm on 5 faces (excluding top face)
Water resistance	Equivalent to IPx2 (Operates normally after being exposed to water dripping at 3mm/min. for at least 2.5 min on each of 4 surfaces tilted at 15°)
Dust resistance	Equivalent to IP5x (Operates normally after 8 hours in a dust chamber containing dust of particle size 75μm or below)

*Confirms the battery operation in tests carried out by Sumitomo.

Does not guarantee that the product is free of faults or damage.

Basic Accessories

Part name	Part No.	Qty.
AC adapter	ADC-1430 series	1 pc
AC power cord	PC-AC<X>*	1 pc
Cooling tray	—	1 pc
Spare electrode	ER-10	1 pair
Operating CD manual	—	1 pc
Quick reference guide	—	1 pc
Carrying case with worktable	CC-Z1	1 pc
Hand strap	—	1 pc
USB cable	—	1 pc

*X=2(American type), 3(CEE type), 5(British type), 6(Oceania type), 7(South African type)

At least, the above basic accessories come with splicer main body.

Some additional accessories may be or may not be included as a splicer standard kit contents. The standard splicer kit contents varies in each region/ country.

Please ask details to your nearest distributors.

Accessories

Part name	Part No.	Remarks
Fiber holder	FHS-025	For φ0.25mm single fiber
	FHS-09	For φ0.9mm single fiber
	FHS-025/LB5	For 0.9mm loose buffered single fiber
	FHD-1	For drop/indoor cable (Cable size : typical 2.0 x 3.1 or 2.6mm)
	1SM-ST	For indoor cable (Cable size : typical 1.6 x 2.0mm)
Battery pack	FHC-3	For 3mm cable
	BU-11/11S	Li-Ion 4600mAh BU-11, 2300mAh BU-11S
	BC-11	—
	Car battery cable	For car battery operation (cigarette socket type)
	PCV-11	—
V-groove cleaning brush	VG-2	Brush for cleaning V-groove
	ER-10	—
Handheld fiber cleaver	FC-7R-F	Automatic blade rotation cleaver
	FC-7M-F8	—
	FC-6S-C	Table-top high precision cleaver
	FC-6RS-C	Automatic blade rotation cleaver
	JR-M03	Jacket remover for single fiber
Jacket remover	LTC-01	—
	HR-3	—
Fiber protection sleeve	FPS-1	60mm, diameter after shrink approx. φ3.2mm
	FPS-40	40mm, diameter after shrink approx. φ3.2mm
	FPS-61-2.6	61mm, diameter after shrink approx. φ2.6mm
	—	—
	—	—




Carrying case with worktable
CC-Z1




Table-top cleaver
FC-6 / FC-6R series



Handy cleaver
FC-7 / FC-7R series



Jacket remover
JR-M03



Available for
Lynx-Custom Fit™
Splice-On Connector



Electrode
ER-10

SUMITOMO ELECTRIC INDUSTRIES, LTD.

Tokyo (Japan)

Sumitomo Electric Industries, Ltd.

Akasaka Center Building, 1-3-13, Motoakasaka,
Minato-ku, Tokyo, 107-8468, JAPAN
TEL: +81-3-6406-2666
<http://global-sei.com/sumitomo-electric-splacers>

London (U.K.)

Sumitomo Electric Europe Ltd.

220 Centennial Park, Centennial Avenue, Elstree,
Herts. WD6 3SL, U.K.
TEL: +44 20-8953-8118
<http://www.sumielectric.com/>

Dubai (U.A.E.)

Middle east office

Dubai Airport Free Zone Phase 4WA,
Office 702 P.O. Box 54890, Dubai, UAE
TEL: +971 4-701-7338