

# RGS-2000NG

## NextGen TCAS Test Set

**COBHAM**

Prepare for Global ATC Modernization  
with NextGen test technology

The most important thing we build is trust



# RGS-2000NG

The premier test solution for development, certification, test and repair of Traffic Collision Avoidance Systems (TCAS) and transponders

# COBHAM

## Features

- 10.4 inch touch screen LCD display for operator control
- Can be remotely controlled via GPIB or Ethernet
- Legacy command set supported for RGS-2000
- Support for current standards:
  - TCAS, DO-185A, DO-185B
  - ADS-B, DO-260, DO-260A, DO-260B
  - TCAS II Hybrid Surveillance, DO-300
  - ATRCRBS/Mode S, DO-181E (option)
- Simulates up to 32 dynamic and 568 static intruders
- Transponder test capability for Modes 3/A, C and S (option)
- ADS-B squitter encode/decode
- Four port antenna simulation
- Contains six transmitters
- Enhanced measurement capabilities
- TX/RX data logging capability

## Applications

- Engineering development, certification, manufacturing and service
- Capable of performing most MOPS tests for DO-185A, DO-185B, DO-260, DO-260A, DO-260B, DO-181E and DO-300

## Benefits

- Replacement for the RGS-2000
- Modern architecture design will support NextGen mandates and future standards changes

## Equipment Tested

- TCAS computers
- ADS-B In Receivers
- ADS-B In Ground Station Receivers
- ADS-R, TIS-B Ground Station Transmitters
- Transponders Mode S/ADS-B Out (transponder option)

See Product Specification Sheet for a more detailed specification.

The RGS-2000NG TCAS Test Set is an RF signal generator/receiver for testing Traffic Alert and Collision Avoidance Systems (TCAS) with an option available for testing transponder LRUs. The RGS-2000NG was designed with modern software-driven digital modulation technology and is the RGS-2000 replacement for engineering development, design validation, manufacturing and return-to-service testing.

## Dimensions

Size: 10.5"H x 19"W x 16.5"D  
26.67 cm x 48.26 cm x 41.9 cm

Weight: 43 lbs. (19.5 kg)

## Environmental

### Temperature

Full specified performance	23 ± 5 degrees C
Operating	0 to 45 degrees C
Storage	-30 to 85 degrees C
Relative Humidity	0 to 95% non-condensing

## VERSIONS, OPTIONS AND ACCESSORIES

Order Number	Description
113956	RGS-2000NG TCAS Test Set (One of the below OEM compatibility options is required)
114343	RGSNGOPT01 - Rockwell Collins compatibility option
114344	RGSNGOPT02 - Honeywell compatibility option
138431	RGSNGOPT03 - Avidyne compatibility option
138453	RGSNGOPT04 - ACSS compatibility option
139363	RGSNGOPT05 - Selex compatibility option
139362	RGSNGOPT06 - Garmin compatibility option
114342	RGSNGOPT10 - Transponder test option

### Standard Accessories

114114	Keyboard w/ touchpad
62302	Power cord, 110V
64020	Power cord set, 220V
139187	Operations Manual (CD)
139190	Getting Started Manual



For further information please contact:

**Cobham AvComm**  
10200 West York Street  
Wichita, KS 67215 USA  
T: (316) 522-4981  
F: (316) 522-1360  
E: [info-test@aeroflex.com](mailto:info-test@aeroflex.com)

or contact your local Cobham AvComm sales office